

For detailed information on these and other types see Data Handbook C22

400 V-range

rated cap. μF	T _{max} mm	H _{max} mm	L _{max} mm	P mm	d mm	MKC cat. number	MKT cat. number
0.01	4.5	10	13	10	0.8	2222 344 51103	2222 344 55103
0.015	4.5	10	13	10	0.8	2222 344 51153	2222 344 55153
0.022	4.5	10	13	10	0.8	2222 344 51223	2222 344 55223
0.033	4.5	10	13	10	0.8	2222 344 51333	2222 344 55333
0.047	5	11	17.5	15	0.8	2222 344 51473	2222 344 55473
0.068	6	12	17.5	15	0.8	2222 344 51683	2222 344 55683
0.1	7	13	17.5	15	0.8	2222 344 51104	2222 344 55104
0.15	8.5	14.5	17.5	15	0.8	2222 344 51154	2222 344 55154
0.22	6.5	15.5	26	22.5	0.8	2222 344 51224	2222 344 55224
0.33	7.5	16.5	26	22.5	0.8	2222 344 51334	2222 344 55334
0.47	9.5	19	26	22.5	0.8	2222 344 51474	2222 344 55474
0.68	11	20	31	27.5	0.8	2222 344 51684	2222 344 55684
1	13	22.5	31	27.5	0.8	2222 344 51105	2222 344 55105

