



HP L1750 and L1950 Flat Panel Monitors

Advanced flat panel technology for mainstream business applications.



The HP L1750 and L1950 Flat Panel Monitors offer advanced features and functionality, superior user comfort design, and the latest technologies suited to a wide variety of users.

What's new

These monitors present several new features over the previous generation of Advantage series LCDs, including:

- **Improved front-of-screen performance:** Both products offer higher contrast ratio (800:1)* and wider viewing angles (160/160 degrees)
- **Privacy filters:** Compatible with privacy filters designed to fit into the monitor bezel
- **Swivel feature:** Allows the monitor panel to be swiveled left to right vs. the whole monitor base
- **Improved cable management:** Routes cables cleanly down the sides and behind the monitor
- **Power button disable:** Allows you to disable the power button, preventing users from turning off the monitor, if desired
- **Power LED on/off control:** Disables the green power light on the front
- **OSD menu rotation:** Rotate the menu into portrait orientation
- **Set Refresh:** Automatically optimize settings

User friendly design and features

Thin bezels on the left and right sides of the screen allow tiling of several monitors for panoramic viewing with minimal visual disruption between each panel. A built-in USB hub with two USB 2.0 ports offers quick and easy connection to a variety of peripheral devices.

User comfort features

90-degree pivot rotation, along with tilt, swivel, and height adjustment features, lets you customize your viewing position. The height adjustment includes low-point settings which allow the bottom of the monitor to nearly touch the desktop work surface.

Smart software

HP Display LiteSaver allows you to schedule Sleep mode at preset times to help protect against image retention and lower power consumption and energy costs. HP Display Assistant enables monitor adjustment and color calibration through the connected PC.

Service and support

The monitors are backed by extensive testing and comprehensive HP service and support from 65,000 IT service and support professionals in 160 countries around the world.

HP L1750 and L1950 Flat Panel Monitors

	HP L1750 Flat Panel Monitor	HP L1950 Flat Panel Monitor
SKUs	GF904AA#ABA	GG458AA#ABA
Panel type	17-inch diagonal Active Matrix TFT (thin film transistor)	19-inch diagonal Active Matrix TFT (thin film transistor)
Viewable image area	17 in (43.2 cm) (diagonal)	19 in (48.25 cm) (diagonal)
Viewing angle	160° horizontal/160° vertical (10:1 minimum contrast ratio)	
Brightness*	300 nits (cd/m ²)	
Contrast ratio*	800:1	
Response rate*	5 ms (rise + fall)	
Pixel pitch	0.264 mm	0.294 mm
Frequency	24 to 83 kHz horizontal; 50 to 77 Hz vertical	
Native resolution	1280 x 1024 @ 60 Hz (analog and digital)	
Input signal	Two connectors: one 15-pin mini D-sub analog VGA and one DVI-D	
Video cable	15-pin D-sub mini connector; detached	
User controls (on-screen display)	Size and positioning, contrast, brightness, clock, clock phase, selectable color temperature, serial number, mode displayed, sleep timer, input selection, factory reset, individual color contrast, full-screen resolution	
Power consumption	Average: 30 watts; Power-saving mode: < 2 watts; Off mode: < 1 watt	
Built-in power supply	Auto-ranging, 90 to 265 VAC; internal power supply	
Dimensions (h x w x d)	Packaged: 14.9 x 21.1 x 9.2 in (37.8 x 53.7 x 23.4 cm); Unpacked w/stand: 13.8 x 14.9 x 11.9 in (35.1 x 37.7 x 30.1 cm) (lowered); 19.3 x 14.9 x 11.9 in (49.0 x 37.7 x 30.1 cm) (raised); Unpacked w/o stand (head only): 12.5 x 14.9 x 2.2 in (31.6 x 37.7 x 5.7 cm)	Packaged: 22.2 x 16.5 x 9.0 in (56.5 x 42.0 x 22.6 cm); Unpacked w/stand: 14.9 x 16.3 x 11.9 in (37.8 x 41.4 x 30.1 cm) (lowered); 20.0 x 16.3 x 11.9 in (50.8 x 41.4 x 30.1 cm) (raised); Unpacked w/o stand (head only): 16.3 x 13.7 x 2.3 in (41.4 x 34.7 x 5.8 cm)
Weight	Unpacked: 15.0 lb (6.8 kg); Packaged: 20.5 lb (9.3 kg)	Unpacked: 14.3 lb (6.5kg); Packaged: 19.4 lb (8.8 kg)
Base features	Tilt range: -5° to +35° vertical tilt, Horizontal swivel range: -45° to +45°, Pivot rotation: 90° into portrait orientation; Height adjustment range: 5.1 in (13.0 cm), Base: attached	
Options	<p>HP Compaq dc 7800 Series Ultra-slim Desktop Integrated Work Center Stand: Allows mounting of a 17- or 19-inch HP flat panel monitor and an HP Compaq dc7800 Ultra-slim Desktop PC on a single stand for the convenience of an "all-in-one" form factor. Sold separately, part number GN783AA. For more information, see product's QuickSpecs.</p> <p>HP Silver Flat Panel Speaker Bar—Optional; powered directly by the monitor or PC, seamlessly attaches to the monitor's bezel; features dual speakers with full sound range and an external jack for headphones. Sold separately, part number EE418AA. For more information, refer to the product's QuickSpecs.</p> <p>HP Flat Panel Monitor Quick Release—Optional; an easy-to-use, VESA-compliant, flat panel monitor mounting solution that allows you to quickly and securely attach a flat panel monitor to a variety of stands, brackets, arms or wall mounts. Sold separately, part number EM870AA. See product QuickSpecs for available mounting configurations.</p>	
Certification and compliance	Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, ENERGY STAR® Qualified, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 Compliant (Pixel Defect Guidelines), Mexican NOM Approval, MPR-II Compliant, PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 99 or 03 depending on region (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft® Windows® Certification, Windows Vista® Certification	
Warranty	Three years parts, labor, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement options may include second business day on-site service, or next business day direct replacement, at HP's sole discretion.** With direct replacement, HP will ship a replacement display product directly to you. Using the prepaid shipping labels provided, return your failed display to HP in the same packaging as the replacement. Certain restrictions and exclusions apply. For details see your product warranty or contact HP Customer Support.	

*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

**Service levels and response times for HP Care Packs may vary depending on your geographic location. Restrictions and limitations apply. For details, visit www.hp.com/go/carepack.

© 2007 Hewlett-Packard Development Company, L.P. Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the U.S. or other countries. Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit www.hp.com

August 2007

