





These size 0 (32mm x 6.3mm) standard glass fuse links are for protection of telecommunications and light electrical equipment. They have a minimum life of 1,000 hours continuous rated current at 25°C. They blow within 10 seconds a 2 x In (+20% to 0%). The derating for operation at elevated temperatures is: 1.75% per 10°C up to 100°C.

BREAKING CAPACITY 10 x In


VOLTAGE RATING: (see table below)

MARKING: Rated value on cap

**ORDERING REFERENCE: L1055A/CURRENT RATING IN AMPERES** 

## **Current ratings:**

Rating	Rated voltage	Rating	Rated voltage
60 mA	1,000 d.c. 250 a.c.	3 A	32 d.c 150 a.c.
100 mA	1,000 d.c. 250 a.c.	5 A	32 d.c. 60 a.c.
150 mA	1,000 d.c. 250 a.c.	7.5 A	32 d.c. 60 a.c.
250 mA	750 d.c. 250 a.c.	10 A	32 d.c. 60 a.c.
500 mA	300 d.c. 250 a.c.	12 A	32 d.c. 60 a.c.
750 mA	300 d.c. 250 a.c.	15 A	32 d.c. 32 a.c.
1 A	250 a.c. 250 a.c.	20 A	32 d.c. 32 a.c.
1.5 A 2 A	200 d.c. 250 a.c.	25 A	32 d.c. 32 a.c.



NOTE - L1055A/100 and L1055A/150 have been discontiuned