

Order Code:

425CP



Description

This 4kW/2.5kW ballast is available in two versions and replaces the original Power Gems 4kW ballast which first saw service in 1992. The CP Model is for operation at 190 - 260V and meets CE standards, it has a.i.f./ unity power factor correction and diagnostic systems. These ballasts automatically sense the lamp/globe fitted to set 4kW or 2.5kW running. Ballasts are working Arri, CMC, Desisti, LTM, Mole, Strand and Sunray luminaires.

Specification

Max. Lamp Power	4kW	Power Cable	integral
Power Options	4kW/2.5kW	Over Temperature Protection	✓
Low Noise Switch	✓	Line Over-Voltage Protection	>260V
Input Voltage Range (V)	95 - 260	Line Under-Voltage Protection	<190V
Input Circuit Breaker	✓	Luminaire Socket Options	✓
Auto Sense Voltage	n/a	Diagnostic System	✓
Input Apparent Power (VA)	4250	Max. Ambient Temp. °C	45
Input Real Power (VA)	4250	Dimensions mm/inch: Width	235/9.25
Amperage Draw 220/110V (A)	19.3 @ 220V	Height	270/10.6
Power Factor	unity	Depth	380/15
Dimming to 50% power	✓	Weight kg/lbs	15.6/34.3
Running Light	✓	Special Versions/Accessories	DMX

Specification and prices subject to change without notice

