



110 Fairgrounds Dr. • PO Box 188 • Manlius, NY
13104 USA
Phone: (315) 682-9176 • Fax: (315) 682-9160
e-mail: wire@carpentermfg.com •
www.carpentermfg.com

MAIN



MODEL 72B

Twin Blade Rotary Wire Stripper

Designed for stripping larger wires, will process thick or thin insulations, solid or stranded conductors and multiple constructions like coaxial cable. Rotary blade action provides a clean, square strip. Blade depth is secured by a locking screw preventing drift and possible nicking. Interchangeable wire guides for easy cable changeover.

SPECIFICATIONS FOR THE MODEL 72B

Wire Size	.120" to .750" Insulated OD (3mm—19mm)
Strip Length	Up to 5.5" (139.5mm) (Remove stop-rod and post for longer strips)
Voltage	115 VAC, 60 Hz, 1.4 A 220 VAC, 50 Hz, .54 A (Optional)
Warranty	1 Year Limited Warranty
Dimensions	6" H x 9" W x 10.5" D
Weight	11.5 lbs

#3897 TWIN BLADE FACE PLATE WIRE GUIDE LIST

PART NO.	SIZE	PART NO	SIZE
2845120	.120	2845453	.453
2845136	.136	2845468	.468
2845152	.152	2845484	.484
2845169	.169	2845500	.500
2845185	.185	2845515	.515
2845201	.201	2845531	.531

2845218	.218	2845546	.546
2845234	.234	2845562	.562
2845250	.250	2845578	.578
2845265	.265	2845593	.593
2845281	.281	2845609	.609
2845297	.297	2845625	.625
2845312	.312	2845640	.640
2845328	.328	2845656	.656
2845343	.343	2845671	.671
2845359	.359	2845687	.687
2845375	.375	2845703	.703
2845390	.390	2845718	.718
2845406	.406	2845734	.734
2845421	.421	2845750	.750
2845437	.437		

Select wire guide(s) with the smallest ID that slips freely over the insulated OD of the wire to be stripped