



110 Fairgrounds Dr. • PO Box 188 • Manlius, NY
13104 USA
Phone: (315) 682-9176 • Fax: (315) 682-9160
e-mail: wire@carpentermfg.com •
www.carpentermfg.com

MAIN



MODEL 74C

3-in-1 Rotary Coaxial Cable Stripper

Designed to provide fast, economical three-step stripping of coaxial cable. Versatility of a single or twin blade faceplate in any of the three stripping stations provide great flexibility in processing coaxial cable or hook up wires. Interchangeable wire guides and simple blade adjustment facilitate quick changeover from one cable to another.

SPECIFICATIONS FOR THE MODEL 74C

Wire Size (#1877 Single Blade)	.028" to .201" Insulated OD (.7mm—5.1mm)
Wire Size (#2500 Twin Blade)	.028" to .265" Insulated OD (.7mm—6.7mm)
Strip Length	Up to 3" (76.1 mm)
Voltage	115 VAC, 60 Hz, 1.4 A 220 VAC, 50 Hz, .54 A (Optional)
Warranty	1 Year Limited Warranty
Dimensions	6.125" H x 11.750" W x 10.750" D
Weight	13 lbs

#1877 SINGLE BLADE FACE PLATE WIRE GUIDE LIST		#2500 TWIN BLADE FACE PLATE WIRE GUIDE LIST	
PART NO.	SIZE	PART NO	SIZE
1700028	.028	2021028	.028
1700032	.032	2021032	.032
1700036	.036	2021036	.036
1700040	.040	2021040	.040
1700046	.046	2021046	.046
1700052	.052	2021052	.052

1700059	.059	2021067	.067
1700067	.067	2021076	.076
1700076	.076	2021086	.086
1700086	.086	2021098	.098
1700098	.098	2021110	.110
1700110	.110	2021120	.120
1700120	.120	2021136	.136
1700136	.136	2021152	.152
1700152	.152	2021169	.169
1700169	.169	2021185	.185
1700185	.185	2021201	.201
1700201	.201	2021218	.218
		2021234	.234
		2021250	.250
		2021265	.265

Select wire guide(s) with the smallest ID that slips freely over the insulated OD of the wire to be stripped