

KL0609-3 Specification:

- 1: Table Size: 25.6" X 47.25"**
 - 2: X,Y,Z Working Area: 23.6" X 35.4" X 3.7"**
 - 3: X,Y,Z Repositioning Accuracy: ± 0.01 mm**
 - 4: X,Y,Z Traveling Positioning Accuracy: $\pm 0.03/300$ mm**
 - 5: X & Z Axis: Round Linear Fully Supported Bearings, Ball Screw**
 - 6: Y Axis: Rectangular Linear bearings, Ball Screw**
 - 7: Base Structure: Cast Aluminum**
 - 8: Max.Speed Max.Working Speed: 0-3000mm/min**
 - 9: Max.Speed: 0-4000mm/min**
 - 10: Max. Power Consumption: 3 KW**
 - 11: Spindle: 1.5 KW Variable speed, Water Cooled Motor**
 - 12: Spindle Speed: 0-24000r/min**
 - 13: CNC Software: Mach3 with USB connection**
 - 14: X, Y Working Accuracy: < 0.02 mm**
 - 15: Running Condition: Temperature: $0^{\circ}\text{C}\sim 45^{\circ}\text{C}$, Relative Humidity: 30%~75%**
 - 16: Packing Size: 1350 x 1070 x 850mm**
 - 17: Net Weight: 180 Kg**
 - 18: Gross Weight: 220 Kg**
- One-Year Warranty**

